


DIMENSIONI DI INGOMBRO (TLX... - TLX...FGR)



Tipo	DN	Dimensioni di ingombro (mm)																														
		AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	U	V	W	Y	Z
TLX1030R	80	1786	1886	848	30	445	545	1341	540	1816	1219	520	446	500	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	448	329
TLX1030R	100	1786	1886	848	30	445	545	1341	540	1816	1219	520	446	500	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	448	329
TLX1030R	125	1786	1886	848	30	445	545	1341	540	1816	1219	520	446	500	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	478	1175	448	329
TLX1030.1	80	1786	1886	848	30	445	545	1341	540	1816	1219	520	489	541	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	491	399
TLX1030.1	100	1786	1886	848	30	445	545	1341	540	1816	1219	520	489	541	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	491	399
TLX1030.1	125	1786	1886	848	30	445	545	1341	540	1816	1219	520	489	541	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	478	1175	491	399

Le dimensioni CC - U - E - D si riferiscono ai bruciatori con ingombro massimo nei modelli ad aria calda e nella versione meccanica. Nelle versioni standard ed elettroniche queste dimensioni possono essere inferiori.